

GEN-4 SYSTEM CONFIGURATIONS

G4-103 System



Specifications:

- Standard 2U Rack-mount
19" (W) x 22" (D) x 3.5" (H)
- Three GEN-4 Multi-Channel Digital Receiver/DSP Cards
- Single channel of automatic monitoring capability

G4-105 System



Specifications:

- Standard 2U Rack-mount
19" (W) x 22" (D) x 3.5" (H)
- Five GEN-4 Multi-Channel Digital Receiver/DSP Cards
- 16 Channels (minimum) monitoring capability

G4-110 System



Specifications:

- Standard 2U Rack-mount
19" (W) x 22" (D) x 3.5" (H)
- 10 GEN-4 Multi-Channel Digital Receiver/DSP Cards
- 30 Channels (minimum) monitoring capability

G4-115 System



Specifications:

- Standard 5U Rack-mount
19" (W) x 22" (D) x 8.75" (H)
- 15 GEN-4 Multi-Channel Digital Receiver/DSP Cards
- 40 Channels (minimum) monitoring capability

G4-115 Dual-Input System



Specifications:

- Standard 5U Rack-mount
19" (W) x 22" (D) x 8.75" (H)
- 15 GEN-4 Multi-Channel Digital Receiver/DSP Cards, arranged as independent stacks of eight and seven within the chassis
- 20 Channels (minimum) and 16 Channels (minimum) monitoring capability, respectively for the receiver card stacks

G4-125 System



Specifications:

- Standard 5U Rack-mount
19" (W) x 22" (D) x 8.75" (H)
- 25 GEN-4 Multi-Channel Digital Receiver/DSP Cards
- 80 Channels (minimum) monitoring capability

For further information, please contact:
ARGON ST, Inc.
8419 Terminal Road
Newington, VA 22122
PH: (703)550-7000 FAX: (703)541-1554

